

Engineering Analysis with Boundary Elements 30 (2006) 100-106

www.elsevier.com/locate/enganabound

ENGINEERING ANALYSIS with BOUNDARY ELEMENTS

The singular function boundary integral method for a two-dimensional fracture problem

Miltiades Elliotis, Georgios Georgiou *, Christos Xenophontos

Department of Mathematics and Statistics, University of Cyprus, P.O. Box 20537, 1678 Nicosia, Cyprus

Received 27 November 2004; received in revised form 19 August 2005; accepted 4 October 2005 Available online 28 November 2005

Abstract

The singular function boundary integral method (SFBIM) originally developed for Laplacian problems with boundary singularities is extended for solving two-dimensional fracture problems formulated in terms of the Airy stress function. Our goal is the accurate, direct computation of the associated stress intensity factors, which appear as coefficients in the asymptotic expansion of the solution near the crack tip. In the SFBIM, the leading terms of the asymptotic solution are used to approximate the solution and to weight the governing biharmonic equation in the Galerkin sense. The discretized equations are reduced to boundary integrals by means of Green's theorem and the Dirichlet boundary conditions are weakly enforced by means of Lagrange multipliers. The numerical results on a model problem show that the method converges extremely fast and yields accurate estimates of the leading stress intensity factors.

© 2005 Elsevier Ltd. All rights reserved.

Keywords: Biharmonic equation; Boundary singularity; Stress intensity factors; Boundary integral method; Lagrange multipliers

1. Introduction

The elastic field near the tip of a crack in an elastic body is characterized by the *stress intensity factors* (SIFs). These are the coefficients, α_j , that appear in the asymptotic expansion of the Airy stress function *u* near the crack tip, which is of the general form

$$u = \sum_{i=1}^{\infty} \alpha_j r^{\beta_j} f_j(\theta), \tag{1}$$

where (r,θ) denote polar coordinates centered at the crack tip. The eigenvalues β_j and the corresponding eigenfunctions $f_j(\theta)$ are known, whereas the SIFs are unknown, with their values depending on the global problem. The first SIF, a_1 , plays a crucial role in the mathematical description of the propagation of fracture, since

$$K = -\sqrt{2\pi a_1} \tag{2}$$

is the opening mode SIF [10].

In the last few decades, there has been a plethora of work aimed at reliably computing the SIFs. The methods used include the finite element method (FEM) with post-processing [1,2,19,20,22], the FEM with local mesh refinement [17], enriched and generalized finite elements [16,18], the method of fundamental solutions [12], as well as certain versions of the Trefftz method [8,11,13,14].

It should be noted that in most of the methods mentioned above, the SIFs are calculated as a *post-solution* operation, i.e. the solution u is approximated first and the SIFs are then calculated using the approximation to u. If the calculation of the SIFs is the main goal of the computation, then it may be beneficial to use a method in which the SIFs are calculated *directly*. Examples of such methods include the Trefftz method [11,14] and the method of fundamental solutions [12].

The objective of the present work is to extend the singular function boundary integral method (SFBIM) to two-dimensional fracture problems. The SFBIM was originally developed in Ref. [5] to solve Laplacian problems with boundary singularities aiming at resolving the convergence difficulties encountered with standard numerical methods in the vicinity of singular points. In this method, the solution is approximated by the leading terms of the local asymptotic solution expansion, which are also employed to weight the governing equation in the Galerkin sense. Furthermore, the discretized equations are reduced to boundary integrals by means of the divergence theorem, and the Dirichlet boundary conditions are weakly enforced by means of Lagrange multipliers. In addition to reducing the dimension of the

^{*} Corresponding author. Tel.: +357 22892612; fax: +357 22892601. *E-mail address:* georgios@ucy.ac.cy (G. Georgiou).

problem by one, another important feature of the method is that the singular coefficients α_j are calculated directly (i.e. no post-processing is required), together with the discrete Lagrange multipliers. The SFBIM has been applied to various problems with singularities, such as the Motz problem [5], the cracked-beam problem [6], and to Laplacian problems over L-shaped domains [3,4], exhibiting fast convergence and yielding very accurate results, especially for the leading singular coefficients.

Since it yields direct estimates of the SIFs, the SFBIM appears to be an excellent candidate for solving fracture problems, which can be expressed as a biharmonic equation in terms of the Airy stress function. To illustrate the extension of the method to such problems, we have chosen a two-dimensional fracture problem, originally studied by Schiff et al. [17].

2. The model problem and the asymptotic solution

We consider here the model problem studied by Schiff et al. [17], which deals with a two-dimensional solid elastic plate containing a single edge crack, subjected to a uniform inplane load normal to the two edges parallel to the crack, while the remaining edges are stress free (see Fig. 1). Using symmetry, the problem is formulated on $\Omega = (-1, 1) \times (0, 1)$, as a biharmonic equation of the Airy stress function u(x,y), and is depicted graphically in Fig. 2. For simplicity, the load in the original problem from [17] has been taken to be 1.

The resulting boundary value problem is as follows: find *u* such that

$$\nabla^4 u = 0$$
 in $\Omega = (-1, 1) \times (0, 1)$, (3)



Fig. 1. A thin elastic plate with a symmetric crack.

with

$$u = 0, \qquad \frac{\partial u}{\partial y} = 0 \text{ on } S_{A}$$

$$\frac{\partial u}{\partial y} = 0, \qquad \frac{\partial^{3} u}{\partial y^{3}} = 0 \text{ on } S_{B}$$

$$u = 2, \qquad \frac{\partial u}{\partial x} = 2 \text{ on } S_{C}$$

$$u = \frac{1}{2}(x+1)^{2}, \qquad \frac{\partial u}{\partial y} = 0 \text{ on } S_{D}$$

$$u = 0, \qquad \frac{\partial u}{\partial x} = 0 \text{ on } S_{E}$$

$$(4)$$

where $\partial \Omega = S_A \cup S_B \cup S_C \cup S_D \cup S_E$. The asymptotic expansion for *u* in the neigbourhood of the singular point *O* can be expressed in terms of an eigenfunction expansion of the form:

$$u(r,\theta) = \sum_{j=1}^{\infty} [c_j \ W_1^j(r,\theta) + d_j \ W_2^j(r,\theta)] , \qquad (5)$$

where (r,θ) are the polar coordinates centered at *O*, and $c_{j,d_{j}}$ correspond to the even and odd SIFs, respectively (see also Eq. (1.1) in [17]). (Using this notation, we have $a_1 = d_1$ in (2).) In expansion (5), the two sets of the so-called singular functions W_{k}^{j} , k = 1,2, are given by

$$W_k^j \equiv r^{\mu_j + 1} f_k(\theta, \mu_j) , \qquad k = 1, 2$$
 (6)

where

$$f_{1}(\theta, \mu_{j}) = \cos(\mu_{j} - 1)\theta - \cos(\mu_{j} + 1)\theta,$$

$$\mu_{j} = j, \quad j = 1, 2, ... ,$$
(7)

and

$$f_{2}(\theta, \mu_{j}) = \cos(\mu_{j} - 1)\theta - \frac{\mu_{j} - 1}{\mu_{j} + 1}\cos(\mu_{j} + 1)\theta,$$

$$\mu_{j} = j - \frac{1}{2} , \quad j = 1, 2, \dots$$
(8)

We note that the singular functions W_k^j satisfy the PDE (3), as well as the boundary conditions on S_A and S_B .

3. The singular function boundary integral method

In the SFBIM, the solution u is approximated by the leading terms of the asymptotic expansion. By employing the first N_{α} terms in (5), the approximate solution \bar{u} is given by

$$\bar{u} = \sum_{i=1}^{N_{\alpha}} \bar{c}_i W_1^i + \sum_{i=1}^{N_{\alpha}} \bar{d}_i W_2^i,$$
(9)

where \bar{c}_i and \bar{d}_i are the approximations to the SIFs. Obviously, the total number of singular functions involved in the approximation is $2N_{\alpha}$. It should be pointed out that the method is restricted to fracture problems with only one crack for which



Fig. 2. The model fracture problem.

the asymptotic solution is available. Moreover, the proposed approximation (9) is valid only if the domain of the problem is a subset of the domain of convergence of the asymptotic solution. Otherwise, the domain may be partitioned into subdomains over which separate approximations obeying appropriate compatibility conditions along the interfaces should be used.

By applying Galerkin's principle, the governing equation is weighted by the singular functions, which yields the following set of discretized equations:

$$\int_{\Omega} \nabla^4 \bar{u} \ W_k^i \, \mathrm{d}V = 0 \ , \quad i = 1, 2, ..., N_{\alpha}, \quad k = 1, 2.$$

Next, applying Green's theorem twice and taking into account that the singular functions satisfy the governing biharmonic Eq. (3), the above integrals are reduced to boundary ones:

$$\int_{\partial \Omega} \left(\frac{\partial \bar{u}}{\partial n} \nabla^2 W_k^i - \bar{u} \frac{\partial (\nabla^2 W_k^i)}{\partial n} \right) \mathrm{d}S + \int_{\partial \Omega} \left(\frac{\partial (\nabla^2 \bar{u})}{\partial n} W_k^i - \nabla^2 \bar{u} \frac{\partial W_k^i}{\partial n} \right) \mathrm{d}S = 0,$$

for $i=1,2,...,N_{\alpha}$, k=1,2. Now, since W_k^i satisfy exactly the boundary conditions along S_A and S_B , the above integral along these boundary segments is identically zero. Therefore,

$$\int_{S_{\rm C}\cup S_{\rm D}\cup S_{\rm E}} \left(\frac{\partial \bar{u}}{\partial n} \nabla^2 W_k^i - \bar{u} \frac{\partial (\nabla^2 W_k^i)}{\partial n}\right) \mathrm{d}S$$
$$+ \int_{S_{\rm C}\cup S_{\rm D}\cup S_{\rm E}} \left(\frac{\partial (\nabla^2 \bar{u})}{\partial n} W_k^i - \nabla^2 \bar{u} \frac{\partial W_k^i}{\partial n}\right) \mathrm{d}S = 0$$

for $i = 1, 2, \dots, N_{\alpha}, k = 1, 2$.

In the SFBIM, the Dirichlet boundary conditions are imposed by means of Lagrange multipliers. In the case of Laplacian problems, the Lagrange multipliers replace the normal derivative $\partial \bar{u}/\partial n$. In the case of biharmonic problems, another option for the Lagrange multipliers is to replace $\partial \nabla^2 \bar{u}/\partial n$. In the current problem, Dirichlet boundary conditions appear along the three boundary parts of interest, i.e. $S_{\rm C}$, $S_{\rm D}$ and $S_{\rm E}$, where the normal derivative of the solution is also specified. Therefore, Lagrange multipliers have been chosen to replace $\partial \nabla^2 \bar{u}/\partial n$ on boundary parts $S_{\rm C}$, $S_{\rm D}$ and $S_{\rm E}$. These are partitioned into three-node elements and the corresponding Lagrange multipliers, denoted, respectively, by $\lambda_{\rm C}$, $\lambda_{\rm D}$ and $\lambda_{\rm E}$, are expanded in terms of quadratic basis functions M_i :

$$\lambda_{\rm C} = \frac{\partial (\nabla^2 \bar{u})}{\partial x} = \sum_{j=1}^{N_{\lambda_{\rm C}}} \lambda_{\rm C}^j M^j \quad \text{on} \quad S_{\rm C}, \tag{10}$$

$$\lambda_{\rm D} = \frac{\partial (\nabla^2 \bar{u})}{\partial y} = \sum_{j=1}^{N_{\lambda_{\rm D}}} \lambda_{\rm D}^j M^j \quad \text{on} \quad S_{\rm D}, \tag{11}$$

and

$$\lambda_{\rm E} = \frac{\partial (\nabla^2 \bar{u})}{\partial x} = \sum_{j=1}^{N_{\lambda_{\rm E}}} \lambda_{\rm E}^j M^j \quad \text{on} \quad S_{\rm E}, \tag{12}$$

where $N_{\lambda_{\rm C}}$, $N_{\lambda_{\rm D}}$ and $N_{\lambda_{\rm E}}$ are the numbers of the discrete Lagrange multipliers $\lambda_{\rm C}^{j}$, $\lambda_{\rm D}^{j}$ and $\lambda_{\rm E}^{j}$ along the corresponding boundaries. The discrete Lagrange multipliers appear as additional unknowns in the problem. The required $N_{\lambda_{\rm C}} + N_{\lambda_{\rm D}} +$ $N_{\lambda_{\rm E}}$ additional equations are obtained by weighting the Dirichlet boundary conditions along $S_{\rm C}$, $S_{\rm D}$ and $S_{\rm E}$ by the quadratic basis functions M^{i} in the Galerkin sense. The following linear system of $2N_{\alpha} + N_{\lambda_{\rm C}} + N_{\lambda_{\rm D}} + N_{\lambda_{\rm E}}$ discretized equations is thus obtained:

Table 1 Convergence of the leading odd SIFs d_i with $2N_{\alpha}$; $N_{\lambda} = 39$

.

$2N_{\alpha}$	d_1	d_2	<i>d</i> ₃	d_4	<i>d</i> ₅	d_{10}
70	2.12751291	-1.03669169	0.0371710	0.1177493	-0.1227288	-0.01108
80	2.12751343	-1.03669221	0.0371701	0.1177510	-0.1227319	-0.01103
88	2.12751347	-1.03669218	0.0371701	0.1177511	-0.1227313	-0.01103
90	2.12751342	-1.03669217	0.0371701	0.1177510	-0.1227316	-0.01103
92	2.12751342	-1.03669217	0.0371701	0.1177509	-0.1227316	-0.01103
94	2.12751343	-1.03669217	0.0371702	0.1177509	-0.1227315	-0.01103
96	2.12751343	-1.03669217	0.0371702	0.1177509	-0.1227314	-0.01103
100	2.12751343	-1.03669219	0.0371702	0.1177509	-0.1227315	-0.01103
110	2.12751347	-1.03669237	0.0371705	0.1177508	-0.1227315	-0.01102
120	2.12751343	-1.03669229	0.0371705	0.1177508	-0.1227314	-0.01103

(13)

$$\begin{split} &\int_{S_{\rm C}} \left(\lambda_{\rm C} W_k^i - \bar{u} \ \frac{\partial (\nabla^2 W_k^i)}{\partial x} - \nabla^2 \bar{u} \frac{\partial W_k^i}{\partial x} \right) \mathrm{d}y \\ &+ \int_{S_{\rm D}} \left(\lambda_{\rm D} W_k^i - \bar{u} \ \frac{\partial (\nabla^2 W_k^i)}{\partial y} - \nabla^2 \bar{u} \frac{\partial W_k^i}{\partial y} \right) \mathrm{d}x \\ &+ \int_{S_{\rm E}} \left(-\lambda_{\rm E} W_k^i + \bar{u} \ \frac{\partial (\nabla^2 W_k^i)}{\partial x} + \nabla^2 \bar{u} \frac{\partial W_k^i}{\partial x} \right) \mathrm{d}y \\ &= - \int_{S_{\rm C}} 2 \nabla^2 W_k^i \, \mathrm{d}y, \quad i = 1, \dots, N_a, \quad k = 1, 2, \end{split}$$

$$\int_{S_{\rm C}} \bar{u} M^i \, \mathrm{d}y = \int_{S_{\rm C}} 2M^i \, \mathrm{d}y, \quad i = 1, 2, ..., N_{\lambda_{\rm C}}, \tag{14}$$

 $\int_{S_{\rm D}} \bar{u} M^i \, \mathrm{d}x = \int_{S_{\rm D}} \left[\frac{1}{2} (x+1)^2 \right] M^i \, \mathrm{d}x, \quad i = 1, 2, ..., N_{\lambda_{\rm D}},$ (15)

$$-\int_{S_{\rm E}} \bar{u}M^i \,\mathrm{d}y = 0, \quad i = 1, 2, \dots, N_{\lambda_{\rm E}}.$$
 (16)

The above linear system can be written in block form as follows:

$$\begin{bmatrix} K & K_{\rm C} & K_{\rm D} & K_{\rm E} \\ K_{\rm C}^{\rm T} & O & O & O \\ K_{\rm D}^{\rm T} & O & O & O \\ K_{\rm E}^{\rm T} & O & O & O \end{bmatrix} \begin{bmatrix} X_{\bar{c},\bar{d}} \\ A_{\rm C} \\ A_{\rm D} \\ A_{\rm E} \end{bmatrix} = \begin{bmatrix} A \\ C \\ D \\ O \end{bmatrix}, \qquad (17)$$

Table 2

Convergence of the leading even SIFs c_i , with $2N_{\alpha}$; $N_{\lambda} = 39$

$2N_{\alpha}$	<i>c</i> ₁	<i>c</i> ₂	<i>c</i> ₃	c_4	<i>c</i> ₅	c ₁₀
70	0.16676222	0.0624426	-0.1324729	-0.0102230	0.1058502	0.004334
80	0.16676181	0.0624440	-0.1324747	-0.0102203	0.1058466	0.004262
88	0.16676182	0.0624439	-0.1324746	-0.0102211	0.1058471	0.004263
90	0.16676184	0.0624439	-0.1324745	-0.0102208	0.1058474	0.004264
92	0.16676184	0.0624439	-0.1324745	-0.0102208	0.1058474	0.004264
94	0.16676184	0.0624439	-0.1324745	-0.0102209	0.1058472	0.004264
96	0.16676184	0.0624439	-0.1324745	-0.0102208	0.1058471	0.004264
100	0.16676184	0.0624439	-0.1324745	-0.0102207	0.1058470	0.004264
110	0.16676179	0.0624441	-0.1324753	-0.0102196	0.1058450	0.004262
120	0.16676181	0.0624440	-0.1324751	-0.0102200	0.1058457	0.004265

Table 3 Convergence of the leading even SIFs c_i , with N_{λ} ; $N_{\alpha} = 94$

N_{λ}	d_1	d_2	d_3	d_4	d_5	d_{10}	
7+13+7	2.12751309	-1.03669185	0.0371707	0.1177516	-0.1227324	-0.01103	
7 + 17 + 7	2.12751334	-1.03669214	0.0371702	0.1177509	-0.1227318	-0.01103	
7 + 21 + 7	2.12751338	-1.03669217	0.0371702	0.1177507	-0.1227319	-0.01103	
7 + 23 + 7	2.12751343	-1.03669217	0.0371702	0.1177510	-0.1227314	-0.01103	
7 + 25 + 7	2.12751343	-1.03669217	0.0371702	0.1177509	-0.1227315	-0.01103	
7 + 27 + 7	2.12751342	-1.03669217	0.0371702	0.1177509	-0.1227315	-0.01103	
7 + 29 + 7	2.12751347	-1.03669213	0.0371703	0.1177513	-0.1227309	-0.01103	
7+31+7	2.12751346	-1.03669213	0.0371703	0.1177513	-0.1227310	-0.01103	
7 + 33 + 7	2.12751335	-1.03669221	0.0371701	0.1177506	-0.1227324	-0.01103	

N_{λ}	c_1	<i>c</i> ₂	<i>c</i> ₃	c_4	<i>c</i> ₅	<i>c</i> ₁₀
7+13+7	0.16676176	0.0624436	-0.1324753	-0.0102209	0.1058486	0.004267
7 + 17 + 7	0.16676184	0.0624439	-0.1324745	-0.0102207	0.1058479	0.004264
7+21+7	0.16676185	0.0624439	-0.1324744	-0.0102204	0.1058480	0.004266
7+23+7	0.16676185	0.0624439	-0.1324745	-0.0102209	0.1058471	0.004264
7 + 25 + 7	0.16676184	0.0624439	-0.1324745	-0.0102209	0.1058472	0.004264
7+27+7	0.16676184	0.0624439	-0.1324745	-0.0102208	0.1058470	0.004263
7 + 29 + 7	0.16676180	0.0624438	-0.1324748	-0.0102213	0.1058461	0.004263
7+31+7	0.16676181	0.0624438	-0.1324748	-0.0102212	0.1058462	0.004262
7 + 33 + 7	0.16676187	0.0624440	-0.1324743	-0.0102201	0.1058485	0.004262

Table 4 Convergence of the leading even SIFs c_1 with N_{λ} ; $2N_{\alpha} = 94$

where $X_{\bar{c},\bar{d}}$, $\Lambda_{\rm C}$, $\Lambda_{\rm D}$ and $\Lambda_{\rm E}$ are the vectors of unknowns,

$$\begin{split} X_{\bar{c},\bar{d}} &= [\bar{c}_1, \dots, \bar{c}_{N_{\alpha}}, \bar{d}_1, \dots, \bar{d}_{N_{\alpha}}]^{\mathrm{T}}, \qquad \Lambda_{\mathrm{C}} = [\lambda_{\mathrm{C}}^1, \lambda_{\mathrm{C}}^2, \dots, \lambda_{\mathrm{C}}^{N_{\lambda_{\mathrm{C}}}}]^{\mathrm{T}}, \\ \Lambda_{\mathrm{D}} &= [\lambda_{\mathrm{D}}^1, \lambda_{\mathrm{D}}^2, \dots, \lambda_{\mathrm{D}}^{N_{\lambda_{\mathrm{D}}}}]^{\mathrm{T}}, \qquad \Lambda_{\mathrm{E}} = [\lambda_{\mathrm{E}}^1, \lambda_{\mathrm{E}}^2, \dots, \lambda_{\mathrm{E}}^{N_{\lambda_{\mathrm{E}}}}]^{\mathrm{T}}. \end{split}$$

It should be noted that the integrands in Eqs. (13)–(16) are non-singular and all integrations are carried out far from the boundaries causing the singularity. Also, the stiffness matrix in (17) is symmetric and becomes singular if $N_{\lambda} > 2N_{\alpha}$ where $N_{\lambda} = N_{\lambda_{\rm C}} + N_{\lambda_{\rm D}} + N_{\lambda_{\rm E}}$. This last fact will be taken into consideration when choosing specific values for these parameters.

4. Numerical results

In order to implement the SFBIM, the boundary parts $S_{\rm C}$, $S_{\rm D}$ and $S_{\rm E}$ (i.e. the boundary parts away from the singularity) are subdivided into quadratic elements. In particular, we use $N_{\rm C}$ elements for each of the boundaries $S_{\rm C}$ and $S_{\rm E}$ and $N_{\rm D}$ elements for boundary $S_{\rm D}$, which makes the total number of Lagrange multipliers $N_{\lambda} = N_{\lambda_{\rm C}} + N_{\lambda_{\rm D}} + N_{\lambda_{\rm E}} = 2N_{\lambda_{\rm C}} + N_{\lambda_{\rm D}}$ (where $N_{\lambda_{\rm C}} = 2N_{\rm C} + 1$ and $N_{\lambda_{\rm D}} = 2N_{\rm D} + 1$). All integrals are calculated numerically by subdividing each quadratic element into 10 subintervals and using a 15-point Gauss–Legendre quadrature over each subinterval [3,4].

Our numerical experiments indicated that the number of the singular functions $2N_{\alpha}$ should be much greater than the number of Lagrange multipliers N_{λ} , because otherwise the stiffness matrix becomes ill-conditioned. On the other hand, large values of $2N_{\alpha}$ should be avoided because the contributions of the high-order singular functions become either negligible (for r < 1) or very large (for r > 1) beyond the limits double precision can handle. Since, at the moment, no a priori way of choosing the 'optimal' values for N_{λ} and N_{α} exists, we have carried out systematic runs in order to study the effects that the variation of these parameters would have on the numerical results.

The effect of $2N_{\alpha}$ on the leading SIFs can be observed in Tables 1 and 2, which show results obtained with N_{λ} =39. Initially, we observe fast convergence as $2N_{\alpha}$ is increased, but at very high values of the latter (i.e. above $2N_{\alpha}$ =94) slow divergence is observed due to the inaccuracies introduced by the high-order singular functions. Tables 3 and 4 show the

effect of varying $N_{\lambda} = N_{\lambda_{\rm C}} + N_{\lambda_{\rm D}} + N_{\lambda_{\rm E}}$, when $2N_{\alpha} = 94$. Again, fast convergence is observed initially but as N_{λ} approaches the value of $2N_{\alpha}$, the results start diverging slowly.



Fig. 3. Calculated Lagrange multipliers along $S_{\rm C}$, $S_{\rm D}$, $S_{\rm E}$, with $2N_{\alpha} = 94$; $N_{\lambda} = 39$ (solid, $N_{\lambda_{\rm C}} = N_{\lambda_{\rm E}} = 7$, $N_{\lambda_{\rm D}} = 25$) and $N_{\lambda} = 43$ (dashed, $N_{\lambda_{\rm C}} = N_{\lambda_{\rm E}} = 9$, $N_{\lambda_{\rm D}} = 25$).

Table 5 Comparison of converged values of the SIFs with those reported by Li et al. [14]

SIFs	Collocation Trefftz method [14]	SFBIM (present work)
d_1	2.12751351	2.1275134
d_2	-1.0366925	-1.036692
d_3	0.0371711	0.037170
d_4	0.117749	0.11775
d_5	-0.122728	-0.12273
d_6	-0.109909	-0.10991
d_7	-0.002255	-0.00226
d_8	0.006863	0.00686
d_9	-0.005936	-0.00594
d_{10}	-0.011032	-0.01103
c_1	0.1667621	0.166762
<i>c</i> ₂	0.0624433	0.062444
<i>c</i> ₃	-0.1324738	-0.132474
c_4	-0.010221	-0.01022
<i>c</i> ₅	0.105846	0.10585
<i>c</i> ₆	0.031153	0.03115
<i>c</i> ₇	-0.007149	-0.00714
c_8	-0.001684	-0.00169
C9	0.009484	0.00950
<i>c</i> ₁₀	0.004281	0.00426

These computations suggest that the 'optimal' values for the numbers of singular functions and Lagrange multipliers are respectively $2N_{\alpha} = 94$ and $N_{\lambda} = 39$. For higher values of $2N_{\alpha}$ (e.g. $2N_{\alpha} = 120$), satisfactory values of the SIFs are still obtained, but the quality of the global solution is not good. When comparing the performance of the method with that in the case of Laplacian problems [3-6], we note that convergence is slower in the case of the biharmonic equation, which is reasonable since the latter is more complicated than the Laplace equation. If the smoothness of the calculated Lagrange multiplier functions is used as an indication of the quality of the solution, then for the combination of $2N_{\alpha}=94$ and N_{λ} =39, the calculated Lagrange multiplier functions along boundary parts $S_{\rm C}$, $S_{\rm D}$ and $S_{\rm E}$, are the smoothest possible (see Fig. 3). We note that for a slightly different value of N_{λ} the estimated values of the SIFs are essentially unaffected, while the calculated Lagrange multipliers exhibit oscillations.

In Table 5 the converged values of coefficients d_i and c_i , i=1,...,10, obtained with the SFBIM are compared with the most accurate values obtained by the collocation Trefftz method of Li et al. [14], who reported that the leading SIF, d_1 , is converged up to the seventh significant digit. The SFBIM appears to be more accurate as it achieves convergence up to the eighth significant digit. Since Li et al. [14] do not provide information about the convergence of the other SIFs, in Table 5 we tabulate their computed values with one additional digit than the converged values of the SFBIM. Nevertheless, there is excellent agreement between the results of the two methods.

5. Conclusions

The singular function boundary integral method (SFBIM) has been developed for solving two-dimensional fracture

problems in terms of the Airy stress function. In this method, the leading terms of the asymptotic solution are used to approximate the solution and thus the SIFs are calculated directly (i.e. no post-processing of the numerical solution is required). The governing biharmonic equation is weighted by the singular functions in the Galerkin sense, and the discretized equations are then reduced to boundary integrals by means of a double application of the divergence theorem, which leads to a significant reduction in the computational cost. Another attractive feature of the method is that integration is necessary only along boundary parts that are away from the crack tip. The Dirichlet boundary conditions are weakly enforced by means of Lagrange multipliers which, depending on the type of the boundary conditions, may replace either $\partial u/\partial n$ or $\partial \nabla^2 u/\partial n$ in the integrands of the discretized equations. The Lagrange multipliers are calculated together with the SIFs.

The SFBIM has been applied to a model problem proposed by Schiff et al. [17]. The numerical calculations showed that the method converges very fast with the number of singular functions and the number of Lagrange multipliers, and yields accurate estimates of the leading SIFs. The value of the leading SIF, in particular, is converged up to eight significant digits. Our results agree well with the values obtained by Li et al. [14] using the collocation Trefftz method.

References

- Babuška I, Miller A. The post-processing approach in the finite element method — Part 1: Calculation of displacements, stresses and other higher derivatives of the displacements. Int J Numer Meth Eng 1984;20: 1085–109.
- [2] Babuška I, Miller A. The post-processing approach in the finite element method — Part 2: The calculation of stress intensity factors. Int J Numer Meth Eng 1984;20:1111–29.
- [3] Elliotis M, Georgiou G, Xenophontos C. The solution of a Laplacian problem over an L-shaped domain with a singular function boundary integral method. Commun Numer Meth Eng 2002;18:213–22.
- [4] Elliotis M, Georgiou G, Xenophontos C. Solving Laplacian problems with boundary singularities: a comparison of a singular function boundary integral method with the p/hp version of the finite element method. Appl Math Comput 2005; 169: 485–499.
- [5] Georgiou G, Olson L, Smyrlis G. A singular function boundary integral method for the Laplace equation. Commun Numer Meth Eng 1996;12: 127–34.
- [6] Georgiou G, Boudouvis A, Poullikkas A. Comparison of two methods for the computation of singular solutions in elliptic problems. J Comput Appl Math 1997;79:277–90.
- [8] Herrera I, Diaz M. Indirect methods of collocation: Trefftz-Herrera collocation. J Numer Meth Partial Diff Eqns 1999;15:709–38.
- [10] Irwin GR. Analysis of stresses and strains near the end of a crack traversing a plate. Trans ASME J Appl Mech 1957;24:361–4.
- [11] Jin WG, Cheung YK, Zienkiewicz OC. Trefftz method for Kirchoff plate bending problems. Int J Numer Meth Engng 1993;36:765–81.
- [12] Karageorghis A. Modified methods of fundamental solutions for harmonic and biharmonic problems with boundary singularities. J Numer Meth Partial Diff Eqns 1992;8:1–19.
- [13] Lefeber D. Solving problems with singularities using boundary elements. Southampton: Computational Mechanics Publications; 1984.

- [14] Li ZC, Lu TT, Hu HY. The collocation Trefftz method for biharmonic Eqs. with crack singularities. Eng Anal Bound Elem 2004;28:79–96.
- [16] Rahulkumar P, Saigal S, Yunus S. Singular p-version finite elements for stress intensity factor computations. Int J Numer Meth Eng 1997;40: 1091–114.
- [17] Schiff BD, Fishelov D, Whiteman JR. Determination of a stress intensity factor using local mesh refinement. In: Whiteman JR, editor. The mathematics in finite elements and applications III. London: Academic Press; 1979. p. 55–64.
- [18] Schnack E. Singularities of cracks with generalized finite elements. Lect Notes Math 1985;1121:258–77.
- [19] Szabó BA, Yosibash Z. Numerical analysis of singularities in two dimensions, Part 1: Computation of the eigenpairs. Int J Numer Meth Engng 1995;38:2055–82.
- [20] Szabó BA, Yosibash Z. analysis of singularities in two dimensions, Part 2: Computation of generalized flux/stress intensity factors. Int J Numer Meth Engng 1996;39:409–34.
- [22] Tracey DM. Finite elements for determination of crack tip elastic stress intensity factors. J Eng Fract Mech 1971;3:255–65.